K119

1U 4K LED-backlit LCD Console Drawer

CyberView™



Benefits

- 1U 18.4" 4K LCD console drawer
- 3840 x 2160@60Hz native resolution/ 1.07B colors
- Display port 1.2 video input / USB KB/MS
- 104-key USB keyboard with either touchpad or trackball
- Built-in dual stereo speakers
- Short depth design of 460mm
- One Man installation design
- Enhanced aesthetics with new molded front panel and 2-point lock
- 2-year standard warranty (upgradable up to 5 years)
- TAA Compliant

Options

- HDMI 2.0 video input **(HDMI)**
- 3G / HD / SD-SDI Broadcast-grade input + Speakers **(SDI)**
- Front USB hub port for device access **(USB)**
- DC power : 12V / 24V / 48V / 125V / 250V



Product Specifications

Console Port	
Video input	Display port 1.2
KB / MS	USB inrerface
DP console 6ft cable : CX-6DP	Drawer end : DP + USB type A x 2 Server end : DP + USB type A x 2

LED-backlit LCD Panel	
Panel size (diagonal)	18.4"
Native resolution	3840 x 2160@60Hz
Brightness (cd/m²)	300
Contrast ratio (typ.)	1000 : 1
Colors	1.07B
Viewing angle (L/R/U/D)	85/85/85/85
Response time (ms)	15
Dot pitch (mm)	0.1065
Display area (mm)	408.96H x 230.04V
Surface treatment	Anti-glare
Surface hardness	3H
MTBF (hrs)	30,000

Physical		
Product (W x D x H)	Single console	442 x 460 x 44 mm 17.4 x 18.1 x 1.73 inch
	Console w/ KVM	442 x 580 x 44 mm 17.4 x 22.8 x 1.73 inch
Packing (W x D x H)	Single console / Console w/ KVM	590 x 808 x 140 mm 23.2 x 31.8 x 5.5 inch
Net weight	Single console	11.5 kg / 25.3 lb
	Console w/ KVM	12.5 kg / 28 lb
Gross weight	Single console	16 kg / 35.2 lb
	Console w/ KVM	18.1 kg / 39.8 lb

*** All dimensions stated are subject to change if options are selected / integrated to base model part codes**

Video Option		
Digital	HDMI	HDMI 2.0 / HDCP 2.2

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 40W / Max. 57W
	Power saving mode	Max. 2W / Max 18W
	Power button off	Max. 1W / Nil

Environment	
Operating temp.	-20 to 70°C degree
Storage temp.	-20 to 70°C degree
Operating humidity	10 ~ 90%, non-condensing
Storage humidity	5 ~ 95%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Compliance	
EMC	FCC & CE
Safety	CE / LVD & UKCA
Environment	REACH & RoHS3 / WEEE


Mounting Distance	
Single console drawer	470 ~ 700 mm 18.5 ~ 27.6 inch
Console w/ KVM drawer	470 ~ 800 mm 18.5 ~ 31.5 inch

Copyright 2026 Austin Hughes Electronics Ltd. All rights reserved.

K119 models w/ KVM

** Resolution related to LCD specification

HDMI KVM	IP	Remote	8-port
	0	0	K119 - 801K



HDMI USB KVM Cable



CK - 6H (6 ft)
4K HDMI - HDMI cable




CK - 6P (6 ft)
4K HDMI - DP cable



CH - 6D (6 ft)
2K HDMI - DVI-D cable

DP KVM	IP	Remote	8-port
	0	0	K119 - 801DP



DP USB KVM Cable


Resolution Support ** : 16:9 - max. 3840 x 2160
16:10 - max. 1920 x 1200




CK - 6DP (6 ft)
4K DP - DP cable


Standard Keyboard

Ge G keyboard with touchpad





Gb G keyboard with trackball





Supporting layouts

America	U.S.				
EMEA	U.K.	Germany	France	Spain	Italy
Asia	Japan	Korea			

The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication. All brand names, logo and registered trademarks are properties of their respective owners.

Copyright 2026 Austin Hughes Electronics Ltd. All rights reserved.