

ePowerSwitch 1G

Power input	1 IEC320 EN60320 C14 (M) Nominal voltage: 230V / 50Hz Max. current: 10A
Power output	1 IEC320 EN60320 C13 (F) Nominal voltage: 230V / 50Hz Max. current: 10A
Network standards	IEEE 802.3, 10/100 Mbit/s
Network protocols	TCP/IP, HTTP
Network connection	RJ45 for UTP CAT5
Max. network cable length	100 m
Terminal connection	RS232, SUB D9 female
Connection Bus	RS485, RJ45
LED	Power, Network, Socket
Operating temperature	0°C to +40°C
Operating humidity	10% to 80%
Dimensions (W x H x D)	185 x 43 x 103
Weight	1 kg
Approvals	CE, EN55022 & EN55024, RoHS
Guarantee	2 years repair/replace

ePowerSwitch 4M+

Power input	1 x IEC320 EN60320 C14 (M) 10A Nominal voltage: 230V / 50Hz Max. current: 10A
Power output	4 x IEC320 EN60320 C13 (F) Nominal voltage: 230V / 50Hz Max. current/outlet: 10A
Network standards	IEEE 802.3, 10/100 Mbit/s
Network protocols	TCP/IP, HTTP
Network connection	RJ45 for UTP CAT5
Max. network cable length	100 m
Terminal connection	RS232, SUB D9 female
Connection Bus	RS485, RJ45
LED	Power, Network, Socket
Operating temperature	0°C to +40°C
Operating humidity	10% to 80%
Dimensions (W x H x D)	230 x 42x112
Weight	1 kg
Approvals	CE, EN55022 & EN55024, RoHS
Guarantee	2 years repair/replace

ePowerSwitch 8M+

Power input	2 x IEC320 EN60320 C14 (M) 10A Nominal voltage: 230V / 50Hz Max. current: 10A
Power output	8 x IEC320 EN60320 C13 (F) Nominal voltage: 230V / 50Hz Max. current/outlet: 10A
Network standards	IEEE 802.3, 10/100 Mbit/s
Network protocols	TCP/IP, HTTP
Network connection	RJ45 for UTP CAT5
Max. network cable length	100 m
Terminal connection	RS232, SUB D9 female
Connection Bus	RS485, RJ45
LED	Power, Network, Socket
Operating temperature	0°C to +40°C
Operating humidity	10% to 80%
Dimensions (W x H x D)	437 x 42x107
Weight	2 kg
Approvals	CE, EN55022 & EN55024, RoHS
Guarantee	2 years repair/replace